

Item no. 94998702

Jumper type FM SC-CXJ59-FM SC/W/CX3/0.2
Cable jacket PVC

Cable min. bend radius 63 mm

Frequency Range	0.3 - 3000 MHz
Impedance (Nom.)	75 Ω
Amp. Rating (measured)	5,5 A @10°C increase
(calculated)	7,5 A @20°C increase
Transfer Impedance (CoMeT)	5 mΩ/m @ 5-30MHz
	1,0 mΩ/item @ 5-30MHz
Shielding Effectiveness (CoMeT)	>90 dB @ 30-1000MHz
	>85 dB @ 1000-3000MHz



All tests performed using instruments calibrated in accordance to our ISO 9001 certification. Further technical specifications and installation instructions can be obtained on request.

Return Loss (IEC 61169-1)
(Rhode und Schwarz ZVB-8)

	Better than	Typical
0.3 - 500 MHz	-30 dB	-33,3 dB
500 - 860 MHz	-30 dB	-33,3 dB
860 - 1000 MHz	-30 dB	-33,3 dB
1000 - 1750 MHz	-27 dB	-30,2 dB
1750 - 2150 MHz	-26 dB	-29,4 dB
2150 - 3000 MHz	-24 dB	-27,1 dB

Insertion Loss Max.

	Better than	Typical
0.3 - 500 MHz	-0,10 dB	-0,05 dB
500 - 860 MHz	-0,11 dB	-0,06 dB
860 - 1000 MHz	-0,11 dB	-0,06 dB
1000 - 1750 MHz	-0,13 dB	-0,08 dB
1750 - 2150 MHz	-0,14 dB	-0,09 dB
2150 - 3000 MHz	-0,16 dB	-0,11 dB

Temperature

Installing	-5° to +50° C
Operating	-40° to +70° C
Storing	-40° to +70° C

Intermodulation

3rd Order (@2x100mW)	IM3	IP3-value
	-124 dBc	+90 dBm

Inner Conductor Resistance

(@ 1 A DC)	<7,1 mΩ
------------	---------

Sealing Test

(IEC IP-code)	**
---------------	----

Insulation Resistance

(@ 500 VDC)	>200 GΩ
-------------	---------

O-rings

-

Dielectric Strength

DC Test Voltage	2 KV
-----------------	------

Base Material

Body Parts	CuZn39Pb3 / CuBe2 / POM / Al-foil / CU braid
Inner Conductor	CU

Max. Tensile Strength

Overall	95 N
---------	------

Plating

Body Parts	Nitin-6
Inner Conductor	-

Torsional Strength

(Connector / Cable)	* NATM
---------------------	--------

Insulators

PE

Test performed by

Sven-Erik Sandberg

Date of release

December 21, 2010

Remarks

* Not Able To Measure(NATM): The cable starts to twist without the connector loosing its grip.
** 1meter@ 24 hours with SEAL RING 1/2" FOR F CONN(99900902).

ISO 9001:2000 / ISO 14001 certified

Distributor:

CABELCON
connectors

Corning Cabelcon ApS, Industriparken 10, DK 4760 Vordingborg
Tel: +45 55 98 55 99 · Fax: + 45 55 98 55 04
E-mail: cabelcon@cabelcon.dk · www.cabelcon.dk

Form 041 rev 7