

CCHE Panel, LC duplex CCHE Panel, LC duplex

CORNING

Part Number: CCHE-CP24-04

The panels are used with field-installable connectors or in applications where the preconnectorized cables are routed directly from the equipment to the piece of inter-connect hardware. This provides an efficient way to securely mate two or more connectors.

Closet connector housing panels are offered in 6-, 8-, 12-, 16- and 24-fiber panels for use with the LANscape® solutions hardware products. The panels are used with field-installable connectors or in applications where the pre-connectorized cables are routed directly from the equipment to the inter-connect hardware. The panels are available with a variety of industry-standard adapter types. In most applications, the closet connector housing panels are designed for applications where specified labeling and connector identification are required. This is accomplished by the use of colored icons with different symbols molded into the icon.



Features and Benefits

Designed to accommodate all industry-standard adapter types

Unique colour-coded connector labeling system

Universal approach is used; one panel size fits in all standard LANscape® Solutions hardware

Available in 6-, 8- and 12-fiber count options in most adapter styles; 16- and 24-fiber count options available in MT-RJ and LC duplex styles

Also available for copper modules 12-fibre ST® Compatible Connector Panel, 12-fibre SC Duplex Panel, 24-fibre MT-RJ Connector Panel; 36-, 72- and 144-fibre count options available only with MTP® adapters

CCHE Panel, LC duplex CCHE Panel, LC duplex



Specifications

Design - Adapter	
Adapter Housing Color	Blue
Adapter Housing Material	Composite
Keyed adapter	No
Shuttered adapter	No
Adapter Type	LC duplex
Insert Material	Ceramic

Design	
Fiber Count	24
Color	Black
Number of Adapters	12
Housing Material	High-grade steel

General Specifications	
Fiber Category	Single-mode (OS2)

Cable Design	
Fiber Count	24

Shipping Dimensions	
Height	250

CCHE Panel, LC duplex CCHE Panel, LC duplex



Shipping Dimensions

Width	190
Depth	180

Dimensions

Length	155
Width	35

Ordering Information

Weight	0.08 kg
Shipping Weight	0.3 kg
Units per Delivery	1/1



Corning Optical Communications GmbH & Co. KG • Lelpziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea