



## Central programável AVANT 12 PRO para canais terrestre, com 32 filtros digitais e programação auto/avançada através do ASuite (Bluetooth®)

Multi-input multiband amplifier, perfect for individual or MDU (Multi Dwelling Unit) terrestrial installations, that allows individual programming of channels available on 4 VHF+UHF (DTT) inputs, in a total of 32 digital filters. The multiband amplifier has 5 inputs, configurable in 2 distribution modes: FM-4x[VHF+UHF] or FM-DAB-3xUHF, and can achieve programmable amplification and balancing of the different RF inputs. In addition, it includes 4G/5G filtering, making the device discriminate by itself the programming of the filters up to channel 48 (LTE700).

Thanks to the built-in **Bluetooth®** antenna, it is possible to carry out advanced programming of the multiband amplifier wirelessly from a smartphone or tablet (Android/iOS), with the **ASuite** application. With this application, the professional user can perform a wide range of functions:

- Channel filter programming
- Channel level autoadjust for balancing all filters
- Manual fine-adjust after the autoadjust for each channel separately
- Activation of the antenna powering

In addition, the PRO model also includes an **autoprogramming** function, executable from ASuite, with which the device uses its intelligence and programs itself, searching and selecting the most outstanding channels and, afterwards, balancing the signal level between them. This model also allows monitoring of the VHF/UHF signal and generation of an installation report (PDF file).

RED compliant

---

<b>Ref.</b>	532203
<b>Logical ref.</b>	AVANT12PRO
<b>EAN13</b>	8424450320471

---

## Packaging info

---

<b>Box</b>	1 pcs.
------------	--------

---

## Physical data

---

<b>Net weight</b>	982.00 g
<b>Gross weight</b>	1,150.00 g
<b>Width</b>	200.00 mm
<b>Height</b>	44.00 mm
<b>Depth</b>	123.00 mm
<b>Main product weight</b>	924.00 g

---

## Highlights

---

- With the **ASuite** application, advanced programming of the device can be carried out wirelessly (**Bluetooth®**), easily and conveniently from a smartphone or tablet (Android/iOS)
- Single device with **2 distribution modes**: 4 inputs support VHF/UHF, or one input is for DAB and

the other 3 for UHF

- **High output level:** up to 124dB $\mu$ V (DIN45004B), to reach a large number of outlets
- **Autoprogramming:** with this function available in ASuite, the device performs channel assignment and level adjustment by itself, as well as activating the antenna powering when it detects that the signal requires it
- Up to **32 individually programmable filters**, with individual digital filtering of each channel, including adjacent channels
- **Digital processing of the channels**, resulting in a perfectly balanced signal level between the different channels at the output
- **Automatic signal regulation** in each filter (AGC). Also allows fine adjust of the output level after regulation
- **High selectivity** VHF/UHF digital filters: >30dB rejection (@ 1MHz)
- SAW (Surface Acoustic Wave) filter for **rejection of 4G/5G signals** from channel 48, with the best selectivity and stability
- **DVB-T and DVB-T2** compatible
- **TForce technology:** terrestrial signal level is always balanced and adjusted to the optimum value
- Power supply at the inputs for **antenna powering**, when the signal requires it
- **LED status indicator** as well as physical autoadjust button built into the control panel
- High shielding chassis (Zamak) to **protect against electromagnetic interference**
- **Very light and compact size** for a high performance control unit (196x122x43mm)
- **100% European design and manufacture:** fully automated manufacturing and subjected to rigorous quality controls

## Technical specifications : Ref. 532203

Number of inputs			5	
Number of outputs			1	
Bands		FM	DAB	UHF
Frequency range	MHz	87 ... 108	174 ... 230	470 ... 694
Number of filters		--	1	32
Channels per filter		--	--	1 ... 1
Gain	dB	29	75	78
Gain adjustment range	dB	0 ... 25	--	--
Manual regulation after auto-adjustment	dB	-5 ... 5	-5 ... 5	-3 ... 3
Slope regulation	dB	--	--	0 ... 5
Input level	dB $\mu$ V	79 ... 104	40 ... 100	40 ... 100
Output level DIN45004B	dB $\mu$ V	124	124	124
Output level EN50083	dB $\mu$ V	128	128	128
Programmable output level	dB $\mu$ V	80 ... 108	87 ... 115	90 ... 118
Noise figure	dB	7	7	6
Selectivity	dB	> 20	> 65	> 65
Powering per inputs	Vdc	--	12	--
Max current input	mA	--	70	--
Input voltage	Vac		220 ... 230	
Mains frequency			50 Hz / 60 Hz	
Max. current	mA		165	
Max. power consumption	W		14.9	
Protection index (IP)			20	
Operating temperature	°C		-5 ... 45	