



Televes reserves the right to modify the product

Uninterruptible Power Supply (UPS) 1600VA/1000W ECO 8 IEC C13 Outputs

High performance Uninterruptible Power Supply System for the protection of equipment against power supply problems. The UPS battery provides autonomy in case of power failure. It will keep the equipment running for the safety time required to recover energy.

The UPS is a fundamental component for communications infrastructures, since it guarantees the constant availability of electricity, preventing data loss in the event of a power failure. It is also key to ensuring the proper operation and extend the life of the devices connected to it, as it protects equipment from power rises and falls.

| | |
|---------------------|---------------|
| Ref. | 533010 |
| Logical ref. | USUSV |
| EAN13 | 8424450265666 |

Packing

| | |
|------------|--------|
| Box | 1 pcs. |
|------------|--------|

Physical data

| | |
|---------------------|------------|
| Net weight | 7,506.00 g |
| Gross weight | 8,486.00 g |
| Width | 305.00 mm |
| Height | 81.00 mm |
| Depth | 312.00 mm |

| | |
|----------------------------|------------|
| Main product weight | 7,800.00 g |
|----------------------------|------------|

Highlights

- Efficient electrical design
- EcoControl function to automatically deactivate peripheral devices when the master device is switched off
- Includes high-performance over-voltage protection. Provides protection for data connections such as Ethernet, Internet, and telephone lines
- Periodic battery self-test, which ensures early detection of battery failure
- Equipped with a switch for easy recovery in case of short-circuit or overload
- 8 IEC C13 sockets for equipment connection
- 4 outputs equipped with both over-voltage protection and backup, and 4 outputs with over-voltage protection
- Damaged battery LED and audible alarm

Technical specifications

| | | |
|-----------------------------|-------|-------------------------------------|
| Rating | VA/W | 1600/1000 |
| Nominal input voltage | V | 230 |
| Input voltage | V | 184 - 264 (adjustable to 161 - 284) |
| Output voltage | V | 230 (adjustable to 220 and 240) |
| Frequency | Hz | 50/60 |
| Automatic battery test | | Yes |
| Deep discharge protection | hours | 4 |
| Battery runtime at 50% load | min. | 11 |
| Battery runtime at 70% load | min. | 6 |
| Communication port | Type | USB |