


Datasheet
2024-10-10

Product Type
Product Name
GTIN / EAN
MPN
Market Entry

s28 L
sCharge PoE Fit
4260258610284
sChPoE-Fit-L-0100
January 2021



Description	<p>USB-C Power and Data on IEEE 802.3af/at Power Over Ethernet:</p> <ul style="list-style-type: none"> - PoE+ Adapter with 30 cm USB-C to Lightning® cable; - Fits into a 60 mm deep EU wall box or US single gang wall box; - Two USB-C ports: A for Power or B for Data and Power only; - Cable length can be adjusted; 150 and 250 cm lengths available; - Provides Power Delivery Profiles: 5 volt, 9 volt, 12 volt, 15 volt, and 20 volt - Requires PoE+ or IEEE 802.3at power; - Developed in cooperation between PoE Texas and smart things; - PoE Texas patents pending. <p>This PoE+ Adapter is ideal for wall-mounted tablets or devices, schedulers, Zoom Room, Gotomeeting, Webex, Skype and other video conferencing POS stations and kiosks.</p>
Technical Data	<p>Uplink Port Port: IEEE 802.3af and at full duplex data rate Port USB-C Power: Role swappable, USB 2.0, USB-C PD 3.0 up to 25 watts 95 Mbps LED Indicator: Negotiated power status Operating Temperature: -10°C - 60°C Operating Humidity: 5% - 95% (Non-condensing) PoE Standard: IEEE 802.3af/at/ (PSE) PoE Line Pair: 1/2/3/4/5(+) or 3/6/7/8 (-) USB-C PD Profiles: 5v 2.6 A, 9 v 1.78 A, 12 v 1.34A, 15 v 1.37 A, 20 v 1.15 A</p>
Compatibility	<p>Compatible to any IEEE 802.3af/at PoE switch or injector. Supports all USB-C iPads or Microsoft Surface Go, Samsung Tab A/S and more (not compatible with Samsung 2020 Tab A7 SMT500 models)</p>
Certifications	<p>CE, FCC, RoHS. FC CE</p>
Content	<p>sCharge PoE FIT adapter cable USB-C -> Lightning® 30cm (longer cables available)</p>
Material/ Ecology Packaging	<p>Housing made of plastic and metal RoHS compliant, WEEE registration: DE 64398562 Packaging completely made of cardboard </p>
Measures/ Weight	<p>57 x 44 x 35 mm (HxWxD), 60g (2.4 oz.), 80 g (incl. adapter cable and packaging)</p>
HS Code Country of Origin	<p>85176200 Made in China.</p>