


Article datasheet s39 C

Article: sCharge ACDC-24V-5V-3A
Art. No.: s39 C
Short text I: USB-C power supply with 24V input, 15W
Net weight (kg): 0.05
Gross weight (kg): 0.06



ACDC converter with AC input 24V and 5V output on USB-C. Fits into a 60 mm deep EU wall box or US single gang wall box; two wire cable length 14 cm, USB-C cable length ~ 20 cm.

Compatible:

Devices with 5V USB C connector input and 15W max

NOT compatible to Lightning iPads or iPhones

Technical Data:

Input Voltage Range: AC 16 - 28V or DC 8 - 40V

Output Voltage: 5V DC

Output Current: 3A

Output Power: 15W

Output: USB C jack; cable length ~33 cm

Conversion Efficiency: > 93%

Operating Temperature: -40°C - 80°C

Operating Humidity: 5% - 95% (Non-condensing)

Protection: Over-Current protection, Over Voltage, Over-Heat, Short Circuit,

Anti-Shock, Anti-Dust waterproof IP 65

Ripple: Full Load Test 40 mV

No Load current: 1.4 mA

Approvals:

CE, FCC, RoHS.

Applications:

Ideal for thermostats, Car cameras, Electric motors, Golf carts, Fork lifts, Solar Panel Power systems, Water pumps, Industrial equipment, etc.

Dimensions:

46 x 32 x 18 mm (1.8" x 1.25" x 0.7") without fastening eyelets;

Weight:

60g (2.12 oz)

Custom Tariff Number:

8504 4090

Made in China.